ALTO
MUSIC, PASSION, DESIGN
DISCOVER THE NEW REVOLUTION
THE COMPACT LINE ARRAY SYSTEM BY ALTO
SEIKAKU TECHNICAL GROUP LIMITED
INFO@ALTOPROAUDIO.COM
WWW.ALTOPROAUDIO.COM

DISCOVER THE NEW REVOLUTION

More and more audio array systems are becoming reference equipment for a daily growing number of rental companies.

The great experience in audio field and cabinet design makes ▲LTO proud to introduce the REVO Line Array

Audio systems, specifically developed to offer the best audio solutions according to the different music needs. All REVO systems

put at your disposal versatile and powerful products, where technology and constant research are the key points.

All ▲LTO Line Array system delivers Music, Passion, Design and a lot of Sound.

REVO SUB118P

Vented Subwoofer, Passive or Direct

- Operating Frequency Range: 37Hz - 200Hz (-10dB)
- Frequency Response: 43Hz - 200Hz (+/- 3dB)
- Maximum Peak SPL: 129 dB SPL calculated EIAJ
- Power Rating (AES Standard): 750W / 1500W
- Transducers Low: 18" Subwoofer, 4" high-power voice coil ceramic magnet, weather resistant cone.
- Crossover modes: Passive, Direct with external selector in direct connection
- System Sensitivity (1w@1mt): 97dB SPL, passive version
- Nominal Impedance: 8 Ohms (nominal)
- Suspension / Mounting: Single 36mm pole socket, four integrated point for line array suspension, two handles, two handles wheel
- Enclosure: 18mm calibrated plywood, black finish, perforated metal grille, silver finish.
- Input Connectors: Two SPK N - L 4 type, Passive, Input 1 + / 1 - Output 1 + / 1 - Direct 1 + / 1 - (2 SPK parallel) with external selector
- Dimension (H x W x D): 620 x 620 x 700mm
  (24.4" x 24.4" x 27.5")
- Net Weight: 51.8kg (113.4 lb)

THE COMPACT LINE ARRAY SYSTEM BY ALTO

REVO SAT208P

2-Way, Passive or Bi-Amp, With a Total of Four Speakers Device

Operating Frequency Range: 65Hz - 20KHz (-10dB)
Frequency Response: 77Hz - 18KHz (+/- 3dB)
Maximum Peak SPL: 126 dB SPL calculated EIAJ
Power Rating (AES Standard): 400W / 800W passive mode
Bi - Amp Low 400W / 800W
Bi - Amp High 75W / 150W
Coverage Horizontal: 100 nominal, single unit
Coverage Vertical: 7.5 variable with array configuration
Transducers LowMid: 2 x 8" Mid-Bass, 2" high-power voice coil, Ceramic magnet, weather resistant cone. Impedance 16 Ohms.
Transducers High: 2 x 1, 4" Titanium diaphragm, neodymium magnet, 1" exit. Impedance 16 Ohms.
Crossover modes: Passive or Bi - Amp with external selector
High frequency externally level selector, to be used for Long Throw (+3dB) or Short Throw (0dB)
System Sensitivity (1w@1mt): 97dB SPL, passive version
Bi - Amp Low 97 dB (2 drivers in parallel)
Bi - Amp High 107 dB (2 drivers in parallel)
Nominal Impedance: Passive 8 Ohms
Bi - Amp Low 8 Ohms (2 drivers in parallel)
Bi - Amp High 8 Ohms (2 drivers in parallel)
Suspension / Mounting: Integrated hardware for suspension in Line Array, dual pole socket, two handles
Enclosure: 18mm calibrated plywood, black finish, perforated metal grille, silver finish
Input Connectors: Two Speakon N - L 4 type,
Passive, Input 1 + / 1 - Output 1 + / 1 -
Bi - Amp, Low 1 + / 1 - High 2 + / 2 -
Dimension (H x W x D): 271.5 x 620 x 423.5mm (10.7" x 24.4" x 16.7")
Net Weight: 21.8kg (48.1 lb)

REVO ACCESSORIES

D4

4 - Channel Amplifier

- Power EIAJ @1% THD. Both channels driven: 4 x 750W@4 Ω (EIAJ); 4 x 370W@8 Ω (EIAJ)
- BRIDGE MODE: 2 x 1500W@8 Ω (EIAJ); 2 x 740W@16 Ω (EIAJ)
- Dimensions (WxDxH): 483 x 376 x 88.8mm (19"x14.8"x3.5")
- Weight : 7.9 Kg (17.4lb)

MAXIDRIVE3.4+

3 - Way Stereo - 3 / 4 / 5 / 6 - Way Mono Digital Crossover & Sound Management System

- Delay lines up to 2.5s for each input and up to 300ms for each output
- 128 user presets and 128 card presets by large memory capacity
- Memory card slot for storage of additional presets and transferring data

REVO-CNP

Power and signal distribution panel

REVO SS-50

Stand for one or two SAT 208P

REVO SAT-HD

Hardware to fly SAT 208P

REVO FB-1

Flying bar to fly
SAT208 & SUB118P

REVO SUB-HD

Hardware to fly SUB 118P

REVO SP-1

Speaker pole for satellite & subwoofer separation.
Maximum: 2 SATs

REVO SP-1W

Speaker pole for satellite & subwoofer separation.
Maximum: 2 SATs

REVO SS-50W

Stand for one or two SAT 208P with winch

REVO FC 4SAT

Flight case for 4 SAT 208P

REVO FC 2SUB

Flight case for 2 SUB 118P

REVO HOOK UP CONFIGURTIONS

(12xSAT208P+8xSUB118P)



(8xSAT208P+4xSUB118P)



(12xSAT208P+4xSUB118P)



(4xSAT208P+2xSUB118P)



▲LTO

SEIKAKU TECHNICAL GROUP LIMITED

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD, TAICHUNG 40151, TAIWAN

TEL: 886-4-22313737 - FAX: 886-4-22346757

www.altoproaudio.com - info@altoproaudio.com

Technical Support for all ▲LTO products: techsupport@altoproaudio.com